

SMARTER

Playground Safety Surface System



Safe, slip resistant textured mats do not hold or absorb water

Mats cover loose rubber and have a class II fire code rating

Accessible surface meets ADA requirements

Reduces serious fall injuries

Trained staff can easily install surfacing

Environmentally friendly subsurface uses one recycled tire per square foot



The SMARTE Advantage



Simple Installation

With the help of a Certified SMARTE Supervisor, your crew can easily install the SMARTE System in your playground. The base layer consists of geo-textile bags that arrive pre-filled with rubber mulch. These easy to handle bags ensure that the entire surface of the playground is uniform and has superior fall height protection.

Excellent Durability

The SMARTE System holds up to extreme changes in temperature and weather, as well as sun exposure.

Unique Top Surface

The PEM top matting creates a level surface, which ensures that the entire playground is accessible by wheelchair. In addition, the PEM top matting is permeable and allows water to quickly drain through the SMARTE System into the soil below. The top matting also contains MICRO-CHEK antimicrobial, which works to guard against the growth of mildew, fungi, and bacteria.

Low Maintenance

The surface cleans easily with a wash down. Simply clean off surface debris with a leaf blower.



The SMARTE Playground Safety Surface System meets both the ASTM 1292-99 Head Impact Attenuation Standard and the ASTM 1951-99 Wheelchair Accessibility Standard.

Fall Height Testing Data

Fall Height	HIC	G-Max
8 Feet	414	81
12 Feet	439	73
17 Feet	806	125

For More Information Contact:
LTR Products- www.ltrproducts.com (800) 961-0909